

AD-A266 080

ARMY RESEARCH LABORATORY



Fault Tree Analysis and Extensions of the V/L Process Structure

Lisa K. Roach

ARL-TR-149

June 1993



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

93-13998

93 6 22 028

NOTICES

Destroy this report when it is no longer needed. DO NOT return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U.S. Department of Commerce, 5285 Port Royal Road, Springfield, VA 22161.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

REPORT DOCUMENTATION PAGE

Form Approved OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden to Washington Headduarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Artington, V2. 22202-4302, and to the Office of Mail adventage and Budget. Paperwork Reduction Project (0704-0188), Washington, DC 20503.

Davis Highway, Suite 1204, Arrington, VA 222	02-4302, and to the Office of Maragement and	Budget, Paperwork Reduction Project (0704-0	188), Washington, DC 20503
1. AGENCY USE ONLY (Leave bla	ink) 2. REPORT DATE	3. REPORT TYPE AND DATES	COVERED
	June 1993	Final, June 1992-1	
4. TITLE AND SUBTITLE		1	DING NUMBERS
_	s and Extensions of the		mEA2 2/0 00 112110
Structure			F592-362-80-V2V2 L162618AH80
6. AUTHOR(S)		PR: 1.	L10201GAHOU
Lisa K. Roach		,	
7. PERFORMING ORGANIZATION	NAME(S) AND ADDIESS(ES)	8. PERI	ORMING ORGANIZATION
U.S. Army Research	• • • • • • •		ORT NUMBER
ATTN: AMSRL-SL-BA			
Aberdeen Proving G	round, MD 21005-5068	1	
	•	j	
9. SPONSORING / MONITORING A	GENCY NAME(S) AND ADDRESS(ES		NSORING / MONITORING
U.S. Army Research	Teboratory	AGI	NCY REPORT NUMBER
ATTN: AMSRL-OP-CI-			
	round, MD 21005-5066		ARL-TR-149
Moracen froving of	Culla, IID 21003 3000	1	
11. SUPPLEMENTARY NOTES			
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION / AVAILABILITY	STATEMENT	112h DI	STRIBUTION CODE
THE STATE OF THE S	3/A/Ement	125. 01	STRIBOTION CODE
• -	c release; distributio	n is	
unlimited.		Į	
		i	
		1	
13. ABSTRACT (Maximum 200 woi	ds) The Ballistic Vulne	rability/Lethality Div	ision (BVLD),
Survivability/Lethali	ty Analysis Directorat	e (SLAD), of the Army	Research Laboratory
(ARL) is involved in a	a variety of programs	that require detailed nt. First, the BVLD i	intormation about
		a number of combat sy	
these full-scale test	s, analytical vulnerab	ility analyses are per	formed to aid in the
development of the te	st plan and to provide	insights into possibl	e outcomes. In
addition, the BVLD is	implementing the Degr	aded States Vulnerabil	ity Methodology
(USVM) for a variety (of combat systems. Bo	th efforts require inf	ormation on the capa-
requirement the RVID	conducts component-la	ssion-essential functi vel vulnerability anal	ons. To satisfy this
		e performance of one o	
tem's combat function	s; these component-lev	el vulnerability analy	ses employ fault tree
analysis to describe,	at the component leve	1, system capabilities	and capability
levels. This report	describes the use of f	ault tree analysis wit	hin the vulner-
ability/lethality (V/) as future efforts.	L) framework and discu	sses applications in o	ther areas as well
as future errorts.			
14. SUBJECT TEHMS			15. NUMBER OF PAGES
-	rocess structure; leth	ality; process	41
structure; fault tre	es; extensions		16. PRICE CODE
			<u> </u>
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
Unclassified	Unclassified	Unclassified	UL

INTENTIONALLY LEFT BLANK.

ACKNOWLEDGMENTS

The author wishes to acknowledge a number of colleagues within the Ballistic Vulnerability Lethality Division upon whose work this report relies heavily: Mr. Joseph Ploskonka of the Vulnerability Methodology Branch, whose criticality analysis of the M1A1 provided the basis for that discussion; Mrs. Stephanie Juarascio, Logistical and Tactical Targets Branch, who performed the NBC Contamination Survivability Degraded States Analysis; Mr. John Abell, Ground Systems Branch, who did much of the work comparing the vulnerability and reliability analyses of the M1A1; Dr. James Walbert, Chief, Air Systems Branch, primary developer of the Vulnerability/Lethality (VL) Process Structure, who provided the discussion of the VL Process Structure as well as technical guidance and comments; and, finally, Dr. Michael Starks, Chief, SLAD Integration Office, who also provided technical guidance and comments.

DTIC QUALITY INSPECTED 2

Acces	sion For	*
Nais	GRA&I	Q
DTIC	TAB	ā
Umanı	rouncud	
Just	fication_	
By	ibution/	
,		
Avad	lability	
	Avoil and	/or
Disc	Special	•
A-1		

INTENTIONALLY LEFT BLANK.

CONTENTS

1.	Introduction	1
2.	V/L Process Structure	1
3.	Criticality Analysis	4
4.	Capability Levels	6
5.	Fault Tree Automation	10
6.	Additional Uses for Fault Tree Analysis	10
	a. RAM Analysis	10
	b. NBC Contamination Survivability	14
	c. ORDs	16
	d. Analytical Versus Experimental Comparisons	17
	e. Force-Level Wargames	18
7.	Future Requirements	18
8.	Summary	18
Re	eferences	21

INTENTIONALLY LEFT BLANK.

LIST OF ILLUSTRATIONS

Figure 1.	The Vulnerability/Lethality Process Structure	3
Figure 2.	Examples of Fault Tree Configurations	5
Figure 3.	Master Power Control Fault Tree	7
Figure 4.	Significant Reduction in Speed Fault Tree	9
Figure 5.	Example Problems from VL/RAM Comparisons	13
Figure 6.	Example of Single System Fault Tree	19

INTENTIONALLY LEFT BLANK.

1. Introduction

The Ballistic Vulnerability/Lethality Division (BVLD), Survivability/Lethality Analysis Directorate (SLAD) of the Army Research Laboratory (ARL) is involved in a variety of programs that require detailed information about the required capabilities of combat equipment. First, the BVLD is conducting a series of full-scale vulnerability tests on a number of combat systems. Prior to these full-scale tests, analytical vulnerability analyses are performed to aid in the development of the test plan and to provide insights into possible outcomes. In addition, the BVLD is implementing the Degraded States Vulnerability Methodology (DSVM) for a variety of combat systems (Abell, Roach, Starks, 1989; Abell, Burdeshaw, Rickter, 1990). Both efforts require information on the capabilities of the combat system to perform mission-essential functions. To satisfy this requirement, the BVLD conducts component-level vulnerability analyses on subsystems of the target, which, if damaged, can affect the performance of one or more of the system's combat functions (Ploskonka, Muehl, and Dively, 1988). These component-level vulnerability analyses employ fault tree analysis to describe, at the component level, system capabilities and capability levels. This report describes the use of fault tree analysis within the vulnerability/lethality (V/L) framework and discusses applications in other areas as well as future efforts/requirements.

2. V/L Process Structure

To understand the value of fault tree analysis one first must have an appreciation of the Vulnerability/Lethality taxonomy as defined by Klopcic, Starks, and Walbert (1992). A brief discussion is provided here.

The basis for the taxonomy of V/L Spaces comes from the recognition that V/L analyses pass through distinct levels of information in a precise order. These levels are:

Level 1: Threat-Target Interaction, or Initial Configuration (including Initial Conditions),

Level 2: Target Component Damage States,

Level 3: Target Capability States, and

Level 4: Target Combat Utility.

From the Target Capability States can be derived the various mission-oriented losses of function such as "Firepower Kill" and "Mobility Kill".

The mappings by which one passes from one level to the next are dependent on different kinds of information at each level. For example, going from Level 1 to Level 2 (threat-target initial configuration to target damage) essentially involves physics; going from Level 2 to Level 3 (target damage to capability) requires engineering measurement. The process is shown pictorially in Figure 1.

It is important at the outset to differentiate between "Levels", which are composed only of states of existence, and the "mappings", operators -- with the data and algorithms to which they have access -- which relate a state at one level to a state at another.

A Level contains all the information required to define the state of the system at the associated stage of a V/L analysis/experiment. At each level, one can define a space of points, each point being a vector whose elements correspond to the status of a particular entity related to the target. For example, in Space 2 (Damage States), each element may refer to the status of a particular component/subsystem. The spaces thus defined are the "V/L Spaces", and represent, at each level, the state of the target system.

A Mapping represents all of the information (physics, e gineering, etc.), known or unknown, required to associate a point in a space at one level with a point in a space at the next level. Mappings have access to information such as: fundamental data (penetration parameters [Level 1 to Level 2], leakage rates [Level 2 to Level 3], etc.); intermediate data generated by the mapping (line-of-sight thicknesses [1 to 2], temperature rise in an uncooled engine [2 to 3]); and algorithms (depth of penetration [1 to 2], fault trees [2 to 3] or [3 to 4]).

The V/L experimental and analytical processes can then be expressed as a series of mappings which relate a state vector in one space (the domain) to a resultant state vector in a next higher-level space (the range).

Note that at each transition to the next level, some detail about the target system may be lost: a broken bolt in Level 2 may be the cause of degraded mobility influencing mission effectiveness, but at Level 3, the bolt is no longer recognized as an entity. It is now widely acknowledged that skipping over levels (such as inferring remaining combat utility directly from the size of the hole in the armor) loses so significant an amount of information that continuity and auditability are lost.

As the taxonomy evolved, its application to areas other than V/L analyses were recognized. These areas include, but are not limited to, Reliability, Availability and Maintainability (RAM) and Battle Damage Repair (BDR) analyses; these will be the subject of discussion later in this paper.

The Vulnerability Process




Figure 1. The Vulnerability/Lethality Process Structure

3. Criticality Analysis

Fault tree analysis, which is used at several levels within the V/L taxonomy just described, has its foundations in reliability theory (Ploskonka, Muehl, and Dively, 1988). First, one can think of a combat system as being composed of a number of systems where each system is a set of components. The performance of a component is binary; that is, the component has a value of "1" if it is functional and "0" if it is nonfunctional. (Note, binary functionality of components and systems is an assumption of the current set of models providing the foundation of this report. One could, given an appropriate continuous function, model functionality as a continuous process.) Additionally, one assumes pairwise independence of the components. Initially, the analytical determination of whether a particular system (or subsystem) is functional starts with connecting all of its components together in the form of a series/parallel construct; these constructs are normally referred to as fault trees. A construct listed in series will fail when at least one of its components fails. For a parallel construct, at least one component in each branch must fail in order for the construct to fail. Many systems, however, consist of both series and parallel constructs; here, a network diagram can be developed to show the functional relationship of the components. This network diagram indicates the system will function if one is able to trace a functioning path from top to bottom. Figure 2 provides examples of different fault tree configurations used by the BVLD; a later subject of this report will be the expansion of these forms to permit modeling of more complex systems. It is noted, though, that a number of sources of subjectivity enter into the process of determining these fault trees; a few are listed here for clarity:


Which components should be included?

- how is this component defined?
- is it critical to system effectiveness?

What constitutes a system?

In vulnerability analysis, the just-described process is referred to as a criticality analysis. A fully functional combat system is analyzed system by system to determine which ones contribute directly to mission functions. Each system is described via a fault tree and, as indicated, is basically the determination of 1) which components, if lost, might result in a reduction of system capability, and 2) the structuring of these "critical" components into a fault tree format. The elements are assumed to be independent and the order within the fault tree is not important (though it should be noted that this assumption does not hold for more general Boolean constructs). The basic idea is to be able to trace a path from the top of the fault tree to the bottom. If no path is found, the functionality enabled by that set of components is lost.

Series Fault Tree Structure



Parallel Fault Tree Structure




Figure 2. Examples of Fault Tree Configurations

A number of criticality analyses have been performed by the BVLD and a portion of one for an armored fighting vehicle (AFV) is provided here as an example. The analysis of the AFV (Ploskonka, Muehl, and Dively, 1988) was conducted with respect to three combat functions: mobility, firepower, and communications. These functions were further divided in the contributing systems for which fault trees were then developed. We will examine one of the subsystems within the mobility function; specifically, a requirement within the electrical power system. In developing the criticality analysis, Ploskonka et al. divided the electrical system into five subsystems, one of which was master power control. Master power control is the set of components required to control the flow of electricity to the vehicle and was determined to have parallel sources for turning on the vehicle master power. Both the commander and driver could turn it on; thus, both of these controls would have to be lost to cut supply of power to the entire vehicle. This functioning is reflected in a parallel construct in the fault tree by including the components for both the commander's and gunner's controls. Furthermore, two other components were deemed essential, the cable 2W103 and the hull networks box. The loss of either would result in loss of vehicle power; each was listed in the fault tree using a series construct. Figure 3 displays the fault tree developed for this subsystem.

This procedure is followed for each identified system. Smaller subsystems composed of critical components are developed first. These subsystems can then be combined in fault trees to represent higher order systems. For example, the master power control subsystem just discussed is part of a more sophisticated system representing electrical power. These fault trees are combined into progressively higher order systems until one sophisticated system is developed for each combat function identified.

The functioning of each system and subsystem is determined by consulting engineering blueprints and by talking to the contractors and the project managers. In their report, Ploskonka, Muchl, and Dively (1988) provide a more detailed discussion of the AFV criticality analysis.

4. Capability Levels

The criticality analysis provides input to live fire test planning in BVLD. It also provides the starting point for defining capability levels, or performance levels, for a combat system for use in the DSVM. The DSVM identifies the required functional capabilities of a combat system (i.e., mobility, firepower, acquisition, etc.). These required capabilities are then further divided into degraded capabilities, within each of the functional categories (i.e., reduced speed, reduced rate of fire, reduced acquisition, etc.), which describe varying degrees of degraded but operational states. Killed components/systems for a given target/warhead interaction are mapped into these degraded capabilities through fault tree analysis. This mapping permits calculation of the probabilities of the combat system being in one or more degraded capabilities. Table 1, provided as an example, lists capability levels for the mobility capability associated with an AFV.

MASTER POWER CONTROL




Figure 3. Master Power Control Fault Tree

TABLE 1. Example Mobility Capability Levels for an AFV

- * No mobility damage
- * Slight reduction in speed (< or = 30%)
- * Significant reduction in speed (> 30%)
- * Total immobilization

A strawman set of fault trees is developed for each capability level. starting with the criticality analysis. For the AFV, the systems developed in the criticality tree were mapped into appropriate capability levels. Different systems can map into the same capability level. For example, both engine power and vehicle electrical power, stems developed in the criticality analysis, map into the "total immobilization" capability level. Similarly, different capability levels can be affected by the same system, e.g., the electric power-hull system affects both "significant reduction of speed" as well as a firepower capability level called "unable to fire on the move". In addition, individual components which, if lost, can result in the achievement of a capability level were also included in the fault trees. The loss of the first hub right would achieve a significant reduction in speed for the AFV and was therefore included in the fault tree. Figure 4 presents the fault tree configuration for "significant reduction in speed".

Once a set of strawman fault trees is developed, the entire set is reviewed for accuracy by experts on the combat system. Their comments and suggestions may be incorporated and the fault trees updated. This finalized set is then used in the DSVM to analyze the residual capability of the combat system after it has encountered a damage mechanism.

A clear advantage of fault tree analysis for both the criticality analysis and the determination of capability level is the auditability and correctability afforded the analyst. Updates or modifications are easily made if changes are required, for example, due to combat system improvements. This process is made simplier by the automation of the fault tree process by the Vulnerability Methodology Branch (VMB) and the Logistics and Tactical Targets Branch (LTTB), both of the BVLD.

State M2 - Reduced Speed, Significant




Figure 4. Significant Reduction in Speed Fault Tree

5. Fault Tree Automation

The process of developing fault trees was automated by VMB through the development of a computer program, called the Interactive Criticality Evaluator (ICE) (Moss, 1985). ICE allows the analyst to visually inspect each fault tree, make any necessary changes and, when satisfied, generate both a pictorial representation of the fault tree and a mathematical equation which describes the Boolean arithmetic. This equation represents the series and parallel logic and can be inserted into any computer code which requires it. For example, within the DSVM, for each capability level articulated, ICE is used to generate both the picture and the mathematical equation. These equations are then inserted in the DSVM, which uses them to evaluate sets of damaged components. Sets of damaged components are mapped through these mathematical equations to determine which capability levels have occurred. Once the appropriate files have been developed on the computer, updates or modifications can be made quickly and easily.

Further automation was accomplished by the LTTB, which created the Interactive Criticality Development Utility (ICU) (Hunt 1992). Similar to ICE, ICU allows users to quickly build fault trees in a Silicon Graphics (SGI) graphics window. ICU creates a pictorial representation as well as assembles the mathematical equations representing the fault tree. Files can be stored and edited as needed.

6. Additional Uses for Fault Tree Analysis

The use of fault tree analysis, however, is not limited to criticality analyses or the DSVM. The premise for this statement can be found in the V/L process structure, discussed earlier in this paper. All events, through the determination of degraded capabilities, are engineering observables or measurables; that is, one could physically observe or measure these phenomena in the field. Consequently, there are a number of additional uses for fault trees that would permit analyses across the spectrum of Army concerns for a combat system based on the same set. This would increase clarity about which capabilities are important and provide a tool for communication among the analysis community. Several such applications will be discussed in this paper. These are the 1) Reliability, Availability, and Maintainability (RAM) analyses; 2) Nuclear, Biological and Chemical (NBC) Contamination Survivability; 3) Operational Requirements Documents (ORDs); 4) comparison of analytical with experimental; and 5) force-level wargames.

a. RAM Analysis. An area the BVLD is investigating is the extension of fault tree analysis to address the problem of RAM. An effort is underway to identify the commonalities between the vulnerability and reliability analysis techniques. The use of fault tree analysis would not only clarify the capabilities of concern for the combat system but provide the same starting point for both vulnerability and RAM analyses. Although the "damage" mechanisms may be

different, the effect on the combat system's functionality should be the same for a given set of lost components. To investigate the feasibility of this proposition, the BVLD, in FY92, formed a working group with the Army Materiel Systems Analysis Activity (AMSAA) Reliability, Availability, and Maintainability Division (RAMD) to address problems such as familiarization with each other's analytical methods and determination of a single nomenclature for use in both V/L and RAM analyses. In addition, the BVLD and RAMD are continuing FY92 work with the U.S. Army Armor School to apply fault tree analysis to the determination of failure criteria for the M1A2 armored fighting vehic'e and the Armored Gun System (AGS).

The initial premise at the beginning of this effort was that the methods for assessing the damage may take different approaches but should yield the same results. Both analyses are concerned with determining remaining combat system capability once a component becomes nonfunctional. That is, both must assess combat system damage. The V/L analyst determines the lethality of a weapon or the vulnerability of a combat system in terms of functional damage; the RAM analyst determines the reliability of the combat system by investigating functional failures. To do this, both analysts must develop an understanding of component interrelationships and relate these components to the system's required capabilities. While the V/L analyst is concerned with critical components, that is, components required to allow mission performance, the RAM analyst is concerned with all components, regardless of the effect on mission performance. For example, the commander's seat is noncritical in terms of mission performance for a V/L analysis and, therefore, is not considered during the analysis. However, a RAM analysis needs to assess the commander's seat in order to determine whether or not it meets its reliability criteria. The components of concern for the V/L analyst are a subset of those of concern to the RAM analyst. Once the capability levels are identified and the fault trees developed, each analyst could select those fault trees applying to his/her analysis.

The objective of the initial BVLD/RAMD investigation, conducted in FY92, was to determine if the two methods yielded the same results and to investigate the differences and similarities in order to determine where the two processes could be combined. The initial effort established the functional loss of the M1A1 for a given set of killed components, selected from a recent vulnerability analysis. This set of killed components was used by both reliability and vulnerability analysts to assess which functions on the vehicle were affected. Each used his normal procedures. For the vulnerability analyst, the criticality analysis of the M1A1 was consulted; a general discussion of criticality analyses was provided earlier in this report. The reliability analyst made use of the RAM-D Failure Criteria Document for the M1E1 tank as well as conversations with the M1A1 project manager. The RAM-D failure criteria use block diagrams which group components by function, e.g., mobility, fire control, etc. This allows the analyst to show the relationship between the function and the components that make up the function. A description is then developed for the block diagram, which contains

narrative representations of the basic functions followed by failure modes of the hardware associated with the function. This description reports which components cause functional loss, functional degradation, or have no effect at all.

Once the individual analyses were completed, the results were compared. Although there appeared to be, in general, no disagreement in assessed functional loss, the different processes and nomenclature made it difficult to be certain. The reliability assessment provided more specific information on functional loss, but required more effort than the vulnerability approach. Generally, the comparisons were fairly straightforward, however, some difficulties did arise. Examples are displayed in Figure 5 with a discussion provided below. The first example lists a specific cable lost. According to the M1A1 criticality analysis, the loss of this cable results in the loss of the gunner's primary sight (GPS) - thermal imaging sight (TIS). The RAM functional loss description reads "1) opens cable disconnection at the thermal receiver, thermal power unit, fire control malfunction will come on: 2) disables power between thermal power control unit and thermal receiver." This represents a fairly good comparison. However, not all were this good. In some instances, components contributed to more than one function and thus were described in more than one narrative section, depending upon the function being described. Unless the RAM analyst knew this a priori, not all lost functions may be identified. For example, one component identified as nonfunctional was the GPS, which is composed of both optics and electronics. Because these are handled separately, the RAM analyst identified functional loss relating to the optics, that is, "loss of day and night target sighting capability for accurate main/coax weapon laying using the GPS"; the electronics were not included. However, the V/L analyst, using the criticality analysis, identified four lost systems: all power traverse, all power elevation, GPS-day and GPS-TIS, and target range. A second, more common problem, dealt with matching functions selected by the analyst when developing their criteria. For example, the loss of the computer electronics unit resulted in the loss of all power elevation and all power traverse in the criticality analysis. The description from the failure criteria document read "loss of ability to calculate ballistic corrections". It's unclear if the two analysts were describing the same functions.

During the conduct of this comparison, it became clear that one set of combat system capabilities should be identified early in the developmental cycle as identification of required combat system capabilities is conducted for all facets of system analyses, to include VL, RAM, and logistics. Techniques employed have not been consistent across organizations, most likely due to a lack of realization by the various analysts/project managers of the inherent similarities, resulting in the development of different capability requirements for different applications. Developing the list of required capabilities early in the cycle would avoid the aforementioned comparison problems as well as provide the basis for all subsequent analyses of the combat system.

Functional Loss

RAM

1/2

Nonfunctional Component

at the thermal receiver, thermal 1) opens cable disconnection thermal power control unit 2) disables power between malfunction will come on power unit, fire control and thermal receiver gunner's primary sight (TIS) (GPS-TIS) cable 1w210-9

GPŚ-day & TIS target range computer electronics all power traverse unit

loss of ability to calculate ballistic corrections

accurate main/coax weapon

laying using the GPS

sighting capability for

all power traverse lost all power elevation lost

loss of day and night target

Figure 5. Example Problems from VL/RAM Comparisons

GPS

These examples indicate that the use of fault tree analysis could make the RAM process easier and faster. Additionally, if fault trees for a given combat system were developed jointly by ARL and AMSAA analysts, early in the analytical process, some of the differences in answers could be avoided, or more easily accounted. As a result, BVLD and RAMD agreed to a joint effort aimed at developing common standards and practices for the identification of required combat system capabilities, the components that contribute to each capability, and the interrelationship of these components to overall system functionality and impact when the component (or subassembly) is lost or partially lost. This effort is intended to develop a standard technique for use by all organizations. Development of this technique will enhance the Army's ability to provide detailed and consistent system capability requirements across the spectrum of analyses. In addition, savings can be identified in terms of both time and money by the reduction of duplication of effort. It is anticipated that this effort will be the starting point for all subsequent combat system analyses to include vulnerability, RAM, logistics, survivability, and effectiveness.

b. NBC Contamination Survivability. The BVLD performed an analysis to determine the effects of the chemical contamination/decontamination cycle on component hardness (Juarascio 1992). One objective of this effort was to assess the feasibility of utilizing the conventional vulnerability tools, i.e., fault trees, ICE/ICU, and the DSVM, in conjunction with the Chemical/Biological Information Analysis Center (CBIAC) database, and if possible, develop a test case example to illustrate the form of the analytical results. The M1A1 tank, the vehicle analyzed in the initial DSVM analysis, was chosen as the illustrative example for the purpose of identifying needed modeling and database improvements to support a robust assessment of the chemical contamination hardness criterion. The use of fault tree analysis and the DSVM lent themselves to this type of analysis because, while the damage mechanisms which cause loss of system functioning vary between chemical and conventional threats, the resultant degradation in system performance, given the loss of the same set of components, should not be different.

Hardness is defined as the ability of a system to withstand the material damaging effects of NBC contamination and the procedures and agents required to decontaminate the item. Materiel developed to perform mission-essential functions shall be hardened to ensure that degradation over a 30-day period of no more than 20% (or other value designated by the combat developer based on approved rationale) in selected quantifiable mission-essential performance characteristics is caused by five exposures to NBC contaminants, decontaminants, and decontaminating procedures encountered in the field (AR 70-71 1984).

The idea was to evaluate different events (either contamination of the item or the subsequent decontamination) and to determine the amount of degradation to susceptible system materials and thus the probability of the critical component failing. The analysis was limited to exterior components for a number of reasons.

First, as this was a test case, the problem was simplified by the exclusion of interior components. Most importantly, though, it eliminated the classification restriction associated with the description of M1A1 interior components.

The exterior components analyzed in this test case were the following: commander's sight, commander's vision blocks, gunner's primary and thermal imaging sights. Of interest was the effect of the chemical agent on the physical properties (transmittance, haze, and resistance to optical abrasion) of the glass portions of these components.

The components were assessed as either failed (combat ineffective) or not failed (combat effective) based on achieving some predefined critical property degradation given specific system application. Using this information, component damage vectors were derived for use in the DSVM. The DSVM mapped these failed components through the capability levels to determine which degradation levels were achieved. The results of the DSVM analysis could then be used to identify whether or not the vehicle met the hardness criterion or to identify benefits of choosing different material types. Although still in progress, initial results of this analysis indicate that the conventional methodology can be adapted for chemical contamination hardness assessment, given sufficient data for the Level 1 to Level 2 mapping become available.

Although not complete, some conclusions can be drawn from this analysis. The prediction of the degraded state of a system; given contamination and decontamination and their estimated frequency of occurrence, given the conditions of evaluation as set forth by the hardness criterion; would allow the project manager to quantify system degradation and provide a means for determining effective ways to maximize system hardness. Establishment of a baseline set of damage vectors and variations on the estimated probabilities of failure as a function of material application could serve to show how changes in material choice would change the baseline frequency distribution. Additionally, variations on the design of the system to introduce system redundancies (as reflected by changes in the fault tree description) could serve to quantify changes in system hardness independent of changes in material choice when perhaps the option to utilize different materials does not exist.

Development of this methodology for NBC contamination survivability assessment would provide an analytical tool for the system designer in determining which component losses will result in failure of the system to meet the NBC contamination hardness criterion. It may then be used to determine improvements in overall system survivability given appropriate changes in material applications or perhaps in system design.

c. ORDs. An additional application of fault trees is the determination of performance criteria for ORDs. Per DOD 5000.2M, an ORD is a formatted statement containing performance and related operational parameters for a proposed concept or system. The initial ORD will describe each concept proposed at Milestone I to include terms of minimum acceptable requirements that define the system capabilities needed to satisfy the Mission Need Statement. The ORD is updated and expanded for Milestone II to include thresholds and objectives for more detailed and refined performance capabilities and characteristics. These updates are based on the results of the trade-off studies and testing conducted during Phase I (Demonstration and Validation). The ORD is then used to develop the system's requirements for contract specification through each acquisition cycle.

One of the major objectives of the ORD is to define the required performance capabilities and requirements. These definitions are to include a performance objective which represents a measurable, beneficial increase in capability or operations and supports the minimum acceptable level specified in the document. Historically, though, these performance objectives have been defined in terms, usually probability of kill (PKs), which are both physically unmeasurable and sufficiently vague in quantification. Because of these inherent problems, definition of the requirements in terms of the system's required capabilities would provide well-defined, measurable performance objectives. As an example, the application of the DSVM approach to the Advanced Field Artillery System (AFAS) will be discussed. This work was initially performed at the direction of the Program and Vulnerability Assessment Office of the Secretary of the Army for Research, Development, and Acquisition (SARDA). (It should be noted that this approach works just as well for lethality [i.e., missiles] as it does for vulnerability/survivability of combat systems. Thus, the use of the term "combat system" implies any system which can be described in terms of required capabilities.)

The AFAS is the future self-propelled howitzer, designed as the replacement for the M109A6 Paladin. The proposed ORD for AFAS was reviewed with selected performance requirements rewritten in terms of required capabilities. As neither the firepower nor the mobility requirements were described in terms of physically measurable quantities, suggestions were made as to how these requirements could be rewritten. Firepower, for example, could be expressed in terms of lower and upper bounds of an acceptable level as shown in Table 2.

TABLE 2. Example Firepower Requirements

Requirement: Rate of Fire

Acceptable levels:

Upper bound: at least 12 rounds/minute for 5 minutes Lower bound: not less than 6 rounds/minute for 5 minutes The same type of physical, or engineering, metric could be applied to the mobility requirement. For example, speed could be defined in terms of the required (and desired) level for different environments, i.e., at least 40 miles/hour in European rolling hills or 25 miles/hour in Southwest Asian desert.

The quantification of the requirement in terms of engineering metrics permits easier evaluation as to whether or not the requirement has been met. The benefits of this approach are numerous. First, the requirements are expressed in terms of capabilities which can be explicitly measured and which are separated into the different capability categories (i.e., mobility, firepower and acquisition). It provides a means for the user to prioritize the capabilities most worth preserving as well as provides greater insight into the military utility of the system. Most importantly, it provides greater clarity as the user and developer of the system discuss trade-offs between what capability is wanted versus what can be affordably built.

d. Analytical Versus Experimental Comparisons. Most of this paper has focused on the analytical techniques employed in vulnerability modeling. However, important applications in the area of experimental data also exist. The approach promulgated in this paper provides an excellent means by which to evaluate both live fire experimental data and potential shot locations prior to actual firings. Pre-shot predictions allow the evaluator to select the most meaningful shots; thus shots which may provide minimal data can be eliminated, or shots which may result in catastrophic loss of the system can be postponed until the end of the shot series.

Most importantly, a combination of experiments and modeling can be employed to maximize the characterization of system performance while minimizing the cost of such characterization. To do so, modeling must be developed such that it parallels the testing process. This, in fact, is the policy of the BVLD as evidenced by the development and promulgation of the V/L Process Structure discussed earlier in this paper. When the modeling parallels testing, one can model a number of threat/target interactions and then do selective testing to see how well the modeling parallels the testing outcome.

The use of fault trees allows one to get to Level 3 in the V/L process as well as provides an interim step between Levels 2 and 4. Modeling from Level 2 to Level 4, as done with the traditional Standard Damage Assessment List (SDAL), does not parallel live fire testing (LFT). Thus, one cannot relate the damage from the LFT to the loss of function value provided by the SDAL or even to battlefield utility; there is no direct comparison between the two. The fault trees, in tandem with the V/L process, provide the means for this direct comparison; it is the inclusion of Level 3 which makes this possible.

e. Force-Level Wargames. The modeling of system functionality with fault trees, in concert with the DSVM, also has consequences for force-level modeling. It permits a more accurate portrayal of the system's remaining capabilities as a result of nonfunctional components, either through combat damage or failure. As currently modeled, the system is either fully functional or fully nonfunctional. A more realistic approach would be to model the system as still functional but in a degraded operational mode. This would result in a system remaining in the engagement longer and possibly affecting the outcome of the game. In addition, information from Level 2, component damage, would provide detailed information on damaged parts, thus providing more accurate data on spare parts requirements and the need for battle damage repair. A joint effort between BVLD and the Training and Doctrine Command (TRADOC) Analysis Center (TRAC) at White Sands Missile Range is currently investigating the inclusion of DSVM metrics in JANUS-A and the resulting affect on the wargame. This effort will provide a clearer picture as to the benefits of fault tree analysis in force-level models.

7. Future Requirements

It is envisioned that the process discussed in this paper can be improved by the inclusion of a continuous function representing component functionality. Although better than previous models, the "go, no go" decision of component functionality is not realistic. A component can suffer damage and still continue to function. For example, how does one handle the problem of a crimped cable when the cable is still functioning though not at 100%. The modeling of such phenomena will be part of the future effort to expand both fault tree analyses and the DSVM as well as the extension of these models to the areas discussed in this report. Current thinking is to allow for additional Boolean arithmetic such as "exclusive or", "maximum" and "minimum. This would permit more detailed and realistic modeling of the combat system and its critical subsystems. In addition, instead of separate fault trees representing capability levels, one extensive event tree could be developed to represent the entire system; branches/nodes could then be weighted according to some mission under consideration. (Note, the event tree would include fault trees representing various system capabilities.) Figure 6 is provided as an example of how this system event tree might look.

8. Summary

Fault tree analysis is a critical part of the vulnerability/lethality framework. It provides the fundamental information on a combat system's subsystem/component interrelationships and its required capabilities as well as a starting point for all subsequent analyses of the system.

As this report discusses, fault tree analysis provides an ideal tool for analyzing a combat system's functionality throughout the various levels of the V/L process structure. To this end, it provides an ideal device for communications




Figure 6. Example of Single System Fault Tree

between concerned participants. The initial effort required to define the fault trees clarifies the required functions of the combat system as well as reduces the need for subjective judgements later in the process. This, in turn, leads to fewer misunderstandings, particularly before major milestones or reviews. The approach also allows V/L modeling to parallel the testing process. As a result, at any level, the modeling can be reviewed for its adequacy in predicting live-fire testing outcomes. In addition, many types of testing may be reduced to determining which trees are broken under initial conditions of interest.

Finally, both fault tree analysis and the general V/L process structure have applications in areas outside the realm of vulnerability/lethality, as evidenced by the discussions within this report. The ability to clarify the operational requirements of a system by identifying its required functions provides a sound basis for communications between the user and the developer throughout the acquisition life cycle of the system. The same analytical approach can be applied to RAM and Battle Damage Repair Analysis (the subject of a forthcoming report) which allows one to evaluate the major aspects of the acquisition cycle using the same process. This overall improvement in communications and analysis can only improve the Army's ability to provide timely, credible analyses.

I. References

- 1. Abell, J.M., L.K. Roach, and M.W. Starks. "Degraded States Vulnerability Analysis." BRL-TR-3010, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, June 1989.
- 2. Abell, J.M., M.D. Burdeshaw, and B.A. Rickter. 'Degraded States Vulnerability Analysis: Phase II." BRL-TR-3161, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, October 1990.
- 3. Ploskonka, J.J., T.M. Muehl, and C.J. Dively. "Criticality Analysis of the M1A1 Tank." BRL-MR-3671, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, June 1988.
- 4. Klopcic, J.T., M.W. Starks, and J.N. Walbert. "A Taxonomy for the Vulnerability/Lethality Analysis Process." BRL-MR-3972, U.S. Army Ballistic Research Laboratory, Aberdeen Proving Ground, MD, May 1992.
- 5. Moss, G.. Internal BVLD documentation on ICE, 1985.
- 6. Hunt, J.E.. "User's Guide and Program Documentation for ICU, an Interactive Criticality Development Utility." U.S. Army Research Laboratory Memorandum Report in progress, Aberdeen Proving Ground, MD, 1992.
- 7. Juarascio, S.S.. "Degraded States of the M1A1 in a Chemical Environment." U.S. Army Research Laboratory Technical Report in progress, Aberdeen Proving Ground, MD, 1992.
- 8. AR 70-71. "Nuclear, Biological, and Chemical Contamination Survivability of Army Materiel." 1 Apr 84.

INTENTIONALLY LEFT BLANK.

No. of		No, of	
Copie	<u>Organization</u>	Copies	Organization
2	Administrator Defense Technical Info Center ATTN: DTIC-DDA Cameron Station Alexandria, VA 22304-6145	1	Commander U.S. Army Missile Command ATTN: AMSMI-RD-CS-R (DOC) Redstone Arsenal, AL 35898-5010
1	Commander	1	Commander U.S. Army Tank-Automotive Command
	U.S. Army Materiel Command ATTN: AMCAM 5001 Eisenhower Ave.		ATTN: ASQNC-TAC-DIT (Technical Information Center) Warren, MI 48397-5000
	Alexandria, VA 22333-0001	1	Director
1	Director U.S. Army Research Laboratory ATTN: AMSRL-OP-CI-AD, Tech Publishing		U.S. Army TRADOC Analysis Command ATTN: ATRC-WSR White Sands Missile Range, NM 88002-5502
	2800 Powder Mill Rd. Adelphi, MD 20783-1145	1	Commandant U.S. Army Field Artillery School ATTN: ATSF-CSI
1	Director U.S. Army Research Laboratory ATTN: AMSRL-OP-CI-AD,	(Class. only)]	Ft. Sill, OK 73503-5000 Commandant
	Records Management 2800 Powder Mill Rd. Adelphi, MD 20783-1145		U.S. Army Infantry School ATTN: ATSH-CD (Security Mgr.) Fort Benning, GA 31905-5660
2	Commander U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-IMI-I Picatinny Arsenal, NJ 07806-5000	(Unclass. only)]	Commandant U.S. Army Infantry School ATTN: ATSH-CD-CSO-OR Fort Benning, GA 31905-5660
2	Commander	1	WL/MNOI Eglin AFB, FL 32542-5000
	U.S. Army Armament Research, Development, and Engineering Center ATTN: SMCAR-TDC		Aberdeen Proving Ground
1	Picatinny Arsenal, NJ 07806-5000 Director	2	Dir, USAMSAA ATTN: AMXSY-D AMXSY-MP, H. Cohen
1	Benet Weapons Laboratory U.S. Army Armament Research,	1	Cdr, USATECOM
	Development, and Engineering Center ATIN: SMCAR-CCB-TL Watervliet, NY 12189-4050	1	ATTN: AMSTE-TC Dir, ERDEC
(Unclass, only) 1	Commander	•	ATTN: SCBRD-RT
	U.S. Army Rock Island Arsenal ATTN: SMCRI-IMC-RT/Technical Library Rock Island, IL 61299-5000	1	Cdr, CBDA ATTN: AMSCB-CI
1	Director U.S. Army Aviation Research	1	Dir, USARL ATTN: AMSRL-SL-I
	and Technology Activity ATTN: SAVRT-R (Library) M/S 219-3 Ames Research Center	10	Dir, USARL ATTN: AMSRL-OP-CI-B (Tech Lib)
	Moffett Field, CA 94035-1000		

<u>Copies</u>	Organization	<u>Copies</u>	Organization
10	CIA	1	Deputy Under Secretary of the Army
	OIR/DB/Standard		for Operations Research
	GE47 HQ		ATTN: SAUS-OR, Hon Walt Hollis
	Washington, DC 20505		The Pentagon, Room 2E660
_	TION A POLICE PRINT COLUMN		Washington, DC 20310-0102
1	HQDA (DAMI-FIT, COL Everson)		Office of the December Director of Defence D&E
	WASH DC 20310-1001	1	Office of the Deputy Director of Defense, R&E ATTN: Dr. William Snowden
1	HODA (DAMO 7D Mr Bionto)		
1	HQDA (DAMO-ZD, Mr. Riente) The Pentagon, Room 3A538		The Pentagon, Room 3D359 Washington, DC 20301
	WASH DC 20310-0410		Washington, DC 20501
	WASH DC 20310-0410	1	Office of the Assistant Deputy Director
1	HQDA (SARD-DO, Mr. Ron Mlinarchik)	•	of Defense, Live Fire Testing
•	WASH DC 20310-0102		ATTN: COL L. Stanford
	Wholi be 20510 0100		The Pentagon, Room 3E1060
1	HQDA (SARD-DOV, COL Steve Dasher)		Washington, DC 20301
-	WASH DC 20310-0103		,,
		1	OUSD(A), DDT&E
1	HQDA (SARD-TT, Mr. Mike Clauson)		ATTN: James O'Bryon
	WASH DC 20310-0103		The Pentagon, Room 3D1084
			Washington, DC 20301-3110
1	HQDA OUSDA(A), DDRE(T&E)		
	ATTN: COL Bernard (Chip) B. Ferguson	1	OUSD(A), DDT&E
	The Pentagon		ATTN: A. Rainis
	WASH DC 20301-3110		The Pentagon, Room 3E1081
_	TYON A OLUMNA (A) DODDON A ARROW		Washington, DC 20301-3110
2	HQDA OUSDA(A), DDRE(R&AT-ET)	•	CAF(AOT (M. Comman)
	ATTN: Mr. Rick L. Menz	1	SAF/AQT (Mr. George Warren)
	Dr. James Short		The Pentagon, Rm BE939 Washington, DC 20330-1000
	The Pentagon, Rm 3D1089 WASH DC 20301-3080		washington, DC 20330-1000
	WASH DC 20301-3000	1	Assistant Deputy Under Secretary
1	HQDA (Limres Study Group)	•	of the Navy
•	ATTN: Shirley D. Ford		ATTN: Fred Crowson
	The Pentagon, Room 1B929		Crystal Plaza 5, Room 162
	WASH DC 20310		2211 Jefferson Davis Highway
			Arlington, VA 22202
1	Office of the Assistant Secretary of the Army		,
	Research, Development, and Acquisition	6	Defense Advanced Research Projects Agency
	ATTN: LTG Cianciolo, Military Deputy		ATTN: Mr. B. Bandy
	Washington, DC 20310-0100		Dr. R. Kahn
			Mr. P. Losleben
1	Office of the Secretary of the Army		Mr. F. Pauen
	Research, Development, and Acquisition		Dr. Reynolds
	ATTN: Deputy for Systems Management,		COL J. Thorpe
	MG Beltson		3701 North Fairfax Dr.
	Washington, DC 20310-0103		Arlington, VA 22203-1714

No. of Copies Organization

2 CIA

ATTN: ORD/PERD, Ray Cwiklinski Tom Kennedy Washington, DC 20505

1 CIA ATTN: ORD/IERD, J. Fleisher Washington, DC 20505

2 ClA

ATTN: OIA.

Barbara A. Kroggel Monica McGuinn Washington, DC 20505

1 CIA ATTN: ORD, Donald Gerson 1820 N. Fort Myer Drive Arlington, VA 22209

1 Chief of Naval Operations OP-332D ATTN: Mr. Chuck Bogner Rm 4D537, The Pentagon Washington, DC 20350-2000

Department of the Navy ATTN: RADM Charles R. McGrail, Jr. The Pentagon, Room 4E536 Washington, DC 20350-2000

Commander
 U.S. Army Materiel Command
 ATTN: AMCDE-PI, Dan Marks
 5001 Eisenhower Ave.
 Alexandria, VA 22333-0001

Headquarters
 U.S. Army Materiel Command
 ATTN: AMCSCI, R. Chait
 5001 Eisenhower Ave.
 Alexandria, VA 22333-0001

Commander
 U.S. Army Materiel Command
 ATTN: AMCPD, Darold Griffin
 5001 Eisenhower Ave.
 Alexandria, VA 22333-0001

No. of Copies Organization

Commander
 U.S. Army Materiel Command
 ATTN: AMCPD-PT, Alan Elkins
 5001 Eisenhower Ave.
 Alexandria, VA 22333-0001

Director
 U.S. Army Research Laboratory
 ATTN: AMSRL-CP-PW, K. Zastrow
 2800 Powder Mill Road
 Adelphi, MD 20783-1145

2 Director
U.S. Army Research Laboratory
ATTN: AMSRL-CP-CE,
J. Predham
D. Smith
2800 Powder Mill Road
Adelphi, MD 20783-1145

Commandant
 U.S. Army Logistics Management College
 ATTN: AMXMC-LS-S, CPT(P) Stephen Parker
 Fort Lee, VA 23801

1 Director
Combat Development
U.S. Army Transportation School
ATTN: COL Elijah Toney
Ft. Eustis, VA 23604

3 Director
U.S. Army Research Office
ATTN: SLCRO-MA,
Dr. J. Chandra
Dr. K. Clark
Dr. Wu
P.O. Boy 12211

P.O. Box 12211 Research Triangle Park, NC 27709-2211

Commander
 U.S. Army Armament Research, Development, and Engineering Center
 ATTN: SMCAR-CCH-V, Paul H. Gemmill Picatinny Arsenal, NJ 07806-5000

No. of Copies Organization

Commander
 U.S. Army Armament Research, Development, and Engineering Center
 ATTN: SMCAR-FSS-E, Jack Brooks
 Picatinny Arsenal, NJ 07806-5000

Commander
 U.S. Army Armament Research, Development,
 and Engineering Center
 ATTN: SMCAR-TD, Jim Killen
 Picatinny Arsenal, NJ 07806-5000

 Commander
 U.S. Army Armament Research, Development, and Engineering Center
 ATTN: SMCAR-TDS, Vic Lindner Picatinny Arsenal, NJ 07806-5000

Commander
 Belvoir Research, Development, and Engineering Center
 ATTN: STRBE-FC, Ash Patil Fort Belvoir, VA 22060-5606

1 Commander Belvoir Research, Development, and Engineering Center ATTN: STRBE-JDA, Melvin Goss Fort Belvoir, VA 22060-5606

1 Commander, USACECOM R&D Technical Library ATTN: ASQNC-ELC-IS-L-R, Myer Center Fort Monmouth, NJ 07703-5000

2 Director Center for Night Vision and Electro-Optics ATTN: AMSEL-RD-NV-V, John Palmer AMSEL-RD-NV-D, Dr. R. Buser Fort Belvoir, VA 22060-5677

Commander
 U.S. Army Foreign Science and Technology
 Center
 ATTN: AIFR, Bill Rich
 Seventh St., NE
 Charlottesville, VA 22901-5396

No. of Copies Organization

Commander
U.S. Army Foreign Science and Technology
Center
ATTN: AIFRS,
T. Walker
Gordon Spencer
AIFRT, John Kosiewicz
AIFRE, S. Eitelman
220 Seventh St., NE
Charlottesville, VA 22901-5396

2 Commander U.S. Army Missile Command ATTN: AMSMI-RD-GC-T, R. Alongi Redstone Arsenal, AL 35898-5000

1 Commander
U.S. Army Missile Command
ATTN: AMSMI-RD-SS-AT, Ed Vaughn
Redstone Arsenal, AL 35898-5000

1 Commander
U.S. Army Missile Command
ATTN: AMSMI-RD, J. Bradas
Redstone Arsenal, AL 35898-5000

Commander
 U.S. Army Missile Command
 ATTN: AMSMI-YTSD, Glenn Allison
 Redstone Arsenal, AL 35898-5070

1 Commander
U.S. Army Missile Command
ATIN: AMSMI-REX, W. Pittman
Redstone Arsenal, AL 35898-5500

Director
U.S. Army Missile and Space Intelligence
Center
ATTN: AIMS-RT, Pat Jordan
Redstone Arsenal, AL 35898-5500

2 Director

U.S. Army Missile and Space Intelligence Center

ATTN: AIMS-YRS.

Thomas Blalock Pete Kirkland

Redstone Arsenal, AL 35898-5500

2 Director

U.S. Army Missile and Space Intelligence Center

ATTN: AIMS-YRT,

Francis G. Cline Don A. Slaymaker

Redstone Arsenal, AL 35898-5500

1 Director

U.S. Army Missile and Space Intelligence

ATTN: Randy L. Smith

Redstone Arsenal, AL 35898-5500

1 Commander

U.S. Army Tank-Automotive Command ATTN: AMCPM-BLK-III, COL Don Derrah Warren, MI 48397-5000

1 Commander

U.S. Army Tank-Automotive Command ATTN: AMSTA-CK, M. Erickson Warren, MI 48090

1 Commander

U.S. Army Tank-Automotive Command ATTN: AMSTA-CR, Mr. Wheelock Warren, MI 48397-5000

1 Commander

U.S. Army Tank-Automotive Command ATTN: AMSTA-CV, COL Becking Warren, MI 48397-5000

2 Commander

U.S. Army Tank-Automotive Command

ATTN: AMSTA-NKS,

D. Cyaye

J. Rowe

Warren, MI 48397-5000

No. of

Copies Organization

2 Commander

U.S. Army Tank-Automotive Command ATTN: AMSTA-RG,

R. Munt

R. McClelland

Warren, MI 48397-5000

3 Commander

U.S. Army Tank-Automotive Command

ATTN: AMSTA-RSC,

John Bennett

Wally Mick

Warren, MI 48397-5000

1 Commander

U.S. Army Tank-Automotive Command ATTN: AMSTA-RSK, Sam Goodman Warren, MI 48090-5000

1 Commander

U.S. Army Tank-Automotive Command ATTN: AMSTA-RY, Ron Beck Warren, MI 48397-5000

2 Commander

U.S. Army Tank-Automotive Command ATTN: AMSTA-ZE, R. Asoklis AMSTA-ZS, D. Rees Warren, MI 48397-5000

1 Office of the PEO, Armored Sys Mod

ATTN: SFAE-ASM-CV, Brian Bonkosky

Warren, MI 48397-5000

1 Commander

HQ, TRADOC

AT N: Assistant Deputy Chief

of Staff for Combat Operations

Fort Monroe, VA 23651-5000

1 Commander

TRADOC

ATTN: ATAN-AP, Mark W. Murray Fort Monroe, VA 23651-5143

 Director
 U.S. Army Cold Regions Research and Development Laboratory
 ATTN: Technical Director, Lewis Link
 Lyme Road
 Hanover, NH 03755

U.S. Army Corps of Engineers
 Assistant Director Research and Development Directorate
 ATTN: Mr. B. Benn
 20 Massachusetts Ave., NW
 Washington, DC 20314-1000

 Commander
 U.S. Army Operational Test and Evaluation Agency
 ATTN: MG Stephenson
 4501 Ford Ave.
 Alexandria, VA 22302-1458

 Commander
 U.S. Army Operational Test and Evaluation Agency
 ATTN: LTC Gordon Crupper
 4501 Ford Ave., #870
 Alexandria, VA 22302-1435

Commander
 U.S. Army Vulnerability Assessment Laboratory
 ATTN: SLCVA-CF, Gil Apodaca
 White Sands Missile Range, NM 88002-5513

2 Director
TRAC-WSMR
ATTN: ATRC-RD, McCoy
ATRC-WEC, P. Shugart
White Sands Missile Range, NM 88002-5502

U.S. General Accounting Office
 Program Evaluation and Methodology Division
 ATTN: Robert G. Orwin
 Joseph Sonnefeld
 Room 5844
 441 G St., NW
 Washington, DC 20548

No. of Copies Organization

 Director
 U.S. Army Model Improvement and Study Management Agency
 ATTN: SFUS-MIS, Eugene P. Visco
 1900 Half Street, SW, Rm L101
 Washington, DC 20324

Director
U.S. Army Industrial Base Engineering Activity
ATTN: AMXIB-MT
AMXIB-PS, Steve McGlone
Rock Island, IL 61299-7260

3 Director U.S. Army Engineer Waterways Experiment Station ATTN: WESEN, Dr. V. LaGarde Mr. W. Grabau WESEN-C, Mr. David Meeker

> P.O. Box 631 Vicksburg, MS 39180-0631

 U.S. Army Engineer Topographic Laboratories ATTN: Technical Director, W. Boge Fort Belvoir, VA 22060-5546

Commander
 Carderock Division
 Naval Surface Warfare Center
 ATTN: Code 1702, Mr. Robert Wunderlick
 Bethesda, MD 20084-5000

1 Commander
Carderock Division
Naval Surface Warfare Center
ATTN: Code 1740.2, Mr. F. Fisch
Bethesda, MD 20084-5000

Director
 Lawrence Livermore National Laboratory
 ATTN: Mark Wilkins, L-3321
 P.O. Box 808
 Livermore, CA 94551

3 Director

Los Alamos National Laboratory
ATTN: MS 985, Dean C. Nelson
MS F600, Gary Tietgen
MS G787, Terrence Phillips

P.O. Box 1663 Los Alamos, NM 87545

1 Director

Los Alamos National Laboratory ATTN: MS F681, LTC Michael V. Zichmn USMC P.O. Box 1668 Los Alamos, NM 87545

1 Director

Sandia National Laboratories Department 913 ATTN: Ron Andreas Albuquerque, NM 87185-5800

1 Director

Sandia National Laboratorics Division 1611 ATTN: Tom James Albuquerque, NM 87185

1 Director

Sandia National Laboratorics Division 1623 ATTN: Larry Hostetler

Albuquerque, NM 87185

Director
Sandia National Laboratories

ATTN: Gary W. Richter

P.O. Box 969 Livermore, CA 94550

Commander

U.S. Naval Air Systems Command JTCG, AS Central Office ATTN: 5164J, J. Jolley Washington, DC 20361

No. of Copies Organization

1 Commander

ADR Program Manager CODE AIR-41112I ATTN: Tom Furlough Naval Air Systems Command Washington, DC 20361-4110

1 Commander

U.S. Naval Ocean Systems Center ATTN: Earle G. Schweizer, Code 000 San Diego, CA 92151-5000

1 Commander

Dahlgren Division U.S. Naval Surface Warfare Center ATTN: Code G13, Tom Wasmund Dahlgren, VA 22448-5000

1 Commander

Dahlgren Division
U.S. Naval Surface Warfare Center
ATTN: Code G102, Glen Hornbaker
Dahlgren, VA 22448-5000

! Commander

Dahlgren Division
U.S. Naval Surface Warfare Center
ATTN: Code J33, George Williams
Dahlgren, VA 22448-5000

2 Commander

U.S. Naval Surface Warfare Center ATTN: Frank Fassnacht, Code N15 Norma D. Holland, Code R-14 10901 New Hampshire Ave. Silver Spring, MD 20903-5070

1 Command-r

Naval Surface Warfare Center ATTN: M. John Timo 10509 Edgefield Drive Adelphi, MD 20783-1130

2 Commander

U.S. Naval Weapons Center ATTN: Code 3951, Jay Butterworth Dr. Helen Wang Bldg. 1400, Room B20 China Lake, CA 93555

5 Commander

U.S. Naval Weapons Center
ATTN: David H. Hall, Code 3181
Mark D. Alexander, Code 3894
Melvin H. Keith, Code 35104
Tim Horton, Code 3386

Robert Cox, Code 3517 China Lake, CA 93555-6001

1 Commander

U.S. Naval Civil Eng Laboratories ATTN: John M. Ferritto, Code L53 Port Hueneme, CA 93043

Naval Postgraduate School
 Department of Aeronautics and Astronautics
 ATTN: Professor Robert E. Ball
 Monterey, CA 93943

Naval Postgraduate School
 Department of Computer Science
 ATTN: Dr. Michael J. Zyda, Code 52
 Monterey, CA 93943-5000

1 Commander
Naval Air Systems Command
ATTN: Philip Weinberg
JTCG/AS5
AIR-516J5
Washington, DC 20361-5160

Commander
 U.S. Naval Sca Systems Command
 ATTN: William G. Boyce, Code 56Y52
 Washington, DC 20362

Commander
 U.S. Naval Sea Systems Command
 ATTN: Granville W. Broome
 SEA 5011
 2521 Jefferson Davis Highway
 Arlington, VA 22202

Commander
 U.S. Naval Sea Systems Command
 ATTN: Philip M. Covich
 SEA 55X
 Washington, DC 20362-5101

No. of Copies Organization

2 Commander U.S. Naval Sea Systems Command ATTN: CPT Charles Calvano USN Robert Keane, Jr. SEA 50 Washington, DC 20362-5101

Commander
 U.S. Naval Sea Systems Command
 ATTN: Oliver F. Braxton
 Donald Ewing, Code 503
 2521 Jefferson Davis Highway
 Arlington, VA 22202

1 Commander
U.S. Naval Sea Systems Command
ATTN: Anthony F. Johnson
SEA 05R2
Washington, DC 20362-5101

Commander
 U.S. Naval Sea Systems Command
 ATTN: CPT William E. Mahew USN
 PMS 423
 Washington, DC 20362-5101

1 Commander
U.S. Naval Sea Systems Command
ATTN: Ca.l H. Pohler, Code 05R23
Washington, DC 20362-5101

1 Commander
U.S. Naval Sea Systems Command
ATIN: CPT R. Percival USN
SEA 05T
2521 Jefferson Davis Highway
Arlington, VA 22202

Commander
 U.S. Space and Naval Warfare Systems
 Command
 ATTN: Paul Wessel, Code 30T
 Washington, DC 20363-5100

1 Office of Naval Technology ATTN: David J. Siegel 800 N. Quincy Street Arlington, VA 22217-5000

No. of		No. of	
	Organization		Organization
335.43		<u>OSP.V</u>	- С
1	Commander	1	Commander
	Eglin Air Force Base		WRDC/AARA
	AD/ENL		ATTN: Michael L. Bryant
	ATIN: Robert L. Stovail		Wright-Patterson AFB, OH 45433
	Eglin AFB, FL 32542		
		1	Commander
1	Commander		FTD/SDMBA
	USAF HQ ESD/PLEA		ATTN: Charles Darnell
	Chief, Engineering and Test Division		Wright-Pauerson AFB, OH 45433
	ATTN: Paul T. Courtoglous		0
	Hanscom AFB, MA 01730	1	Commander
2	Commander		FTD/SDMBU ATTN: Kevin Nelson
2	AFATI.		Wright-Patterson AFB, OH 45433
	ATTN: AGA.		Wingherancison Arb, On 43433
	Lawrence Jones	1	Commander
	Mickie Phipps	•	FTD/SQDRA
	Eglin AFB, FL 32542-5434		ATTN: Greg Koesters
			Wright-Patterson AFB, OH 45433-6508
1	WL/MNMW (Mr. John A. Collins)		
	Eglin AFB, FL 32542	1	Commander
	-		FTD
1	Commander		ATTN: Tom Reinhardt
	AFEWC		Wright-Patterson AFB, OH 45433
	ATTN: AFEWC/SAXE, Bod Eddy		_
	Kelly AFB, TX 78243-5000	1	Commander
•			FTD/SDAEA
1	Commander		ATTN: Joe Sugrue
	AFWAL/AARA ATTN: Ed Zelano		Wright-Patterson AFB, OH 45433
	Wright-Patterson AFB, OH 45433	1	Commander
	Wilght-rancison Arb, Ort 43433	1	AFWAL/AARA
1	Commander		ATTN: Vincent Velten
•	AFWAL/FIES		Wright-Patterson AFB, OH 45433
	ATTN: James Hodges Sr.		Winglis Landson in P., On T. V.
	Wright-Patterson AFB, OH 45433-6523	1	Commander
	•		FTD/SQDRA
2	Commander		ATTN: Larry E. Wright
	AFWAL/MLTC		Wright-Patterson AFB, OH 45433
	ATTN: LT Robert Carringer		
	Dave Judson	1	Commander
	Wright-Patterson AFB, OH 45433-6533		AD/CZL
			ATTN: James M. Heard
1	Commander		Eglin AFB, FL 32542-5000
	ASB/XRM		Comment of the
	ATTN: Gerald Bennett	1	Commander
	Martin Lentz Wright Patterson AFR OH 45433		AD/ENYW
	Wright-Patterson AFB, OH 45433		ATTN: Jim Richardson Eglin AFB, FL 32542-5000
			Egili Ard, FL 34344-3(W

- 1 Commander
 Air Force Armament Laboratory
 ATTN: AFATL/DLY, James B, Flint
 Eglin AFB, FL 32542-5000
- Commander
 U.S. Army FSTC/CA3
 ATTN: Scott Mingledorff
 220 Seventh Avc.
 Charlottesville, VA 22901-5396
- Commander
 U.S. Army FSTC (UK)
 ATTN: MAJ Nigel Williams
 220 Seventh Ave.
 Charlottesville, VA 22901-5396
- Commander
 U.S. Army FSTC
 ATTN: Dr. Tim Small
 220 Seventh Ave.
 Charlottesville, VA 22901-5396
- Director
 Defense Intelligence Agency
 ATTN: DIW-4B3, Jay Hagler
 Washington, DC 20340-6763
- Director
 U.S. Army TRADOC Analysis Command ATTN: ATRC
 White Sands Missile Range, NM 88002-5502
- Director U.S. Army TRADOC Analysis Command ATTN: ATRC-LS, Mr. Greenhill Fort Lee, VA 23801-6140
- Commander
 U.S. Army Combined Arms Combat
 Development Activity
 ATTN: ATZL-CAI-S, Mrs. Durkes
 Fort Leavenworth, KS 66027-5300
- 1 Commander
 U.S. Army Combined Arms Training Activity
 ATTN: ATZL-TAS-P, MAJ Smith
 Fort Leavenworth, KS 66027-7000

- Commandant
 U.S. Army Air Defense Artillery School
 ATTN: ATSA-DTN-SY
 Fort Bliss, TX 79916-7090
- Commandant
 U.S. Army Air Defense Artillery School
 ATTN: ATSA-CDC
 Fort Bliss, TX 79916-7090
- Commandant
 U.S. Army Armor School
 ATTN: ATSB-CD
 Fort Knox, KY 40121-5215
- Commandant
 U.S. Army Chemical School
 ATTN: ATZN
 Ft. McCiellan, AL 30205-5020
- 1 Commandant
 U.S. Army Field Artillery School
 ATTN: ATSF
 Fort Sill, OK 73503-5600
- Commander
 U.S. Army John F. Kennedy Special Warfare
 Center and School
 ATTN: ATSU-CD
 Fort Bragg, NC 28307-5000
- Commandant
 U.S. Army Ordnance Missile and Munitions
 Center and School
 ATTN: ATSK-CD
 Redstone Arsenal, AL 35897-6500
- U.S. Army Signal Center and Fort Gordon ATTN: ATZH-CDC Fort Gordon, GA 30905-5000
- 1 Assistant Commandant
 U.S. Army Transportation School
 ATTN: ATSP-CDC
 Fort Eustis, VA 23601-5393

- 1 Commander
 HQ U.S. Army Aviation Center and Fort Rucker
 ATTN: ATZQ-CDC
 Fort Rucker, AL 36362-5000
- 1 Commander HQ U.S. Army Aviation Center and Fort Rucker ATTN: ATZQ-TDS-SM Fort Rucker, AL 36362-5000
- Director
 U.S. Army Concepts Analysis Agency
 8120 Woodmont Ave.
 Bethesda, MD 20814-2797
- Institute for Defense Analyses (IDA)
 ATTN: Mr. Irwin A. Kaufman
 Mr. Arthur O. Kresse
 1801 N. Beauregard St.
 Alexandria, VA 22311
- 1 Institute for Defense Analyses ATTN: Carl F. Kossack 1005 Athens Way Sun City, FL 33570
- Institute for Defense Analyses
 ATTN: Dr. Natarajan Subramonian
 14309 Hollyhock Way
 Burtonsville, MD 20866
- ADPA
 ATTN: Donna R. Alexander
 Bill King
 Two Colonial Place, Suite 400
 2101 Wilson Blvd.
 Arlington, VA 22201-3061
- ARC Professional Services Group ATTN: Arnold R. Gritzke 5501 Backlick Road 3pringfield, VA 22151
- 2 Aero Corporation ATTN: David S. Eccles Gregg Snyder P.O. Box 92957, M4/913 Los Angeles, CA 90009

- AFELM, The Rand Corporation ATTN: Library-D 1700 Main St. Santa Monica, CA 90406
- 2 Air Force Wright Aeronautical Labs ATTN: CDJ, CPT Jost Josel '1 Faison Wright-Patterson AFB, OH 45433-6523
- Alliant Techsystems, Inc.
 ATTN: Hatem Nasr
 Systems and Research Center
 3660 Technology Drive
 P.O. Box 1361
 Minneapolis, MN 55418
- 2 Alliant Techsystems, Inc. ATTN: Raymond H. Burg Laura C. Dillway MN38-4000 10400 Yellow Circle Drive Minnetonka, MN 55343
- Analysis and Technology
 ATTN: RADM Thomas M. Hopkins USN (Ret)
 1113 Carper St.
 McLean, VA 22101
- 1 Armored Vehicle Technologies ATTN: Coda M. Edwards P.O. Box 2057 Warren, MI 48090
- 1 ASI Systems, International ATTN: Dr. Michael Stamatelatos 3319 Lone Jack Road Encinitas, CA 92024
- Battelle Research Laboratory
 ATTN: TACTEC Library, J. N. Huggins
 505 King Avc.
 Columbus, OH 43201-2693
- Battelle Research Laboratory
 Defense and Space Systems Analysis
 ATTN: Dr. Richard K. Thatcher
 505 King Ave.
 Columbus, OH 43201-2693

- 1 Battelle Research Laboratory ATTN: Bernard J. Tullington 1300 N. 17th St., Suite 1520 Arlington, VA 22209
- Battelle
 Edgewood Operations
 ATTN: Roy Golly
 2113 Emmorton Park Road
 Edgewood, MD 21040
- 1 The BDM Corporation ATTN: Edwin J. Dorchak 7915 Jones Branch Drive McLean, VA 22102-3396
- 1 Bell Helicopter, Textron ATTN: Jack R. Johnson P.O. Box 482 Fort Worth, TX 76101
- 3 BMY, Division of Harsco
 ATTN: William J. Wagner, Jr.
 Ronald W. Jenkins
 Ed Magalski
 P.O. Box 1512
 York, PA 17404
- Board on Army Science and Technology National Research Council Room MH 280
 2101 Constitution Ave., NW Washington, DC 20418
- Boeing Aerospace
 ATTN: Dr. Robert Chiavetta
 MS 8K17
 P.O. Box 3999
 Scattle, WA 98124-2499
- 1 Boeing Military Airplanes ATTN: MS K80-08, Jerry White P.O. Box 7730 Wichita, KS 67277-7730
- Booz-Allen and Hamilton, Inc.
 ATTN: Dr. Richard B. Benjamin
 Suite 131, 4141 Colonel Glenn Highway
 Dayton, OH 45431

- Booz-Allen and Hamilton, Inc. ATTN: Lee F. Mallett
 1300 N. 17th St., Suite 1610
 Rosslyn, VA 22209
- 2 Booz-Allen and Hamilton, Inc. ATTN: John M. Vice WRDC/FIVS/SURVIAC Bldg 45, Area B Wright-Patterson AFB, OH 45433-6553
- John Brown Associates
 ATTN: Dr. John A. Brown
 P.O. Box 145
 Berkeley Heights, NJ 07922-0145
- 1 Chamberlain ATTN: Mark A. Sackett P.O. Box 2545 Waterloo, IA 50704
- Commander
 Combined Arms Combat Development
 ATTN: ATZL-CAP, LTC Morrison
 Director, Surv Task Force
 Fort Leavenworth, KS 66027-5300
- 1 Commander
 Combined Arms Combat Development
 ATTN: ATZL-HFM, Dwain Skelton
 Fort Leavenworth, KS 66027-5300
- Computer Sciences Corporation Integrated Systems Division ATTN: Abner W. Lee
 9668 Highway 20 West, Suite 1 Madison, AL 35758
- 1 CRS Sirrine, Inc. ATTN: Dr. James C. Smith P.O. Box 22427 1177 West Loop South Houston, TX 77227
- Cypress International
 ATTN: August J. Caponecchi
 James Logan
 1201 E. Abingdon Drive
 Alexandria, VA 22314

- Commander
 Naval Surface Warfare Center
 ATTN: UERD, Code 177, Robert E. Fuss
 Portsmouth, VA 23709-5000
- 1 Commander
 Carderock Division
 Naval Surface Warfare Center
 ATTN: Code 1210, Seymour N. Goldstein
 Bethesda, MD 20084-5000
- Commander
 U.S. Army Nuclear and Chemical Command
 ATTN: MONA-CM, J. Walters
 7500 Backlick Rd., Bldg 5073
 Springfield, VA 22150-3198
- 1 Defense Nuclear Agency Structural Dynamics Section ATTN: Tom Tsai Washington, DC 20305
- Denver Research Institute
 BW 228
 ATTN: Lawrence G. Ullyatt
 2050 E. Iliff Ave.
 Denver, CO 80208
- Eichelberger Consulting Company
 ATTN: Dr. Robert Eichelberger, President
 409 West Catherine St.
 Bel Air, MD 21014
- Electronic Warfare Associates, Inc. ATTN: William V. Chiaramonte 2071 Chain Bridge Road Vienna, VA 22180
- 1 Emprise, Ltd ATTN: Bradshaw Armendt, Jr. 201 Crafton Road Bel Air, MD 21014
- Environmental Research Institute of Michigan ATTN: Mr. K. Augustyn
 P.O. Box 134001
 Ann Arbor, MI 48113-4001

- 1 E-OIR Measurements, Inc. ATTN: Russ Moulton P.O. Box 3348, College Station Fredericksburg, VA 22402
- 1 ERIM
 ATTN: Stephen R. Stewart
 Exploitation Applications Department
 Image Processing Systems Division
 P.O. Box 8618
 Ann Arbor, MI 48107-8618
- 1 USA ETL/IAG
 ATTN: Jim Campbell
 Bldg. 2592, Room S16
 Fort Belvoir, VA 22060-5546
- 1 FMC Corporation ATTN: Sidney Kraus 1105 Coleman Ave., Box 1201 San Jose, CA 95108
- 1 FMC Corporation ATTN: Ronald S. Beck 881 Martin Ave. Santa Clara, CA 95052
- BDM International ATTN: Mr. Steve Church, FX2B307 7915 Jones Branch Drive McLean, VA 22102-3396
- 1 BDM International ATTN: Mr. Tom Hooker, FF2B304 7915 Jones Branch Drive McLean, VA 22102-3396
- 1 FMC Corporation Naval Systems Division (NSD) ATTN: MK-45, Randall Ellis 4800 East River Road Minneapolis, MN 55421-1498
- 1 FMC Corporation Northern Ordnance Division ATTN: M3-11, Barry Brown 4800 East River Road Minneapolis, MN 55421-1498

- FMC Corporation
 Ordnance Engineering Division
 ATTN: H. Croft
 M. Hatcher
 1105 Coleman Ave., Box 1201
 San Jose, CA 95108
- 1 GE Aircraft Engines ATTN: Dr. Roger B. Dunn One Neumann Way, MD J185 Cincinnati, OH 45215-6301
- 1 General Dynamics Land Systems ATTN: MZ-4362055, Gary Jackman P.O. Box 2074 Warren, MI 48317
- General Dynamics Corporation ATTN: MZ-2650, Dave Bergman P.O. Box 748
 Fort Worth, TX 76101-0748
- 1 General Motors Corporation Research Laboratories ATTN: J. Boyse Warren, MI 48090
- Allison Gas Turbine Division
 General Motors Corporation
 ATTN: John A. MacBain, Ph.D., Supervisor
 Low Observables Technology
 P.O. Box 420, Speed Code W-16
 Indianapolis, IN 46206-0420
- 1 California Institute of Technology
 Jet Propulsion Laboratory
 ATTN: D. Lewis
 4800 Oak Grove Drive
 Pasadena, CA 91109
- 1 Kaman Sciences Corporation ATTN: Timothy S. Pendergrass 600 Boulevard South, Suite 208 Huntsville, AL 35802
- 1 Ketron, Inc.
 ATTN: Robert S. Bennett
 901 Dulaney Valley Road, Suite 220
 Baltimore, MD 21204-2600

- Logistics Management Institute ATTN: Edward D. Simms Jr. 6400 Goldsboro Road Bethesda, MD 20817-5886
- 1 LTV Aerospace and Defense Company ATTN: Daniel M. Reedy P.O. Box 655907 Dallas, TX 75265-5907
- 1 Martin Marietta Aerospace ATTN: MP-113, Dan Dorfman P.O. Box 555837 Orlando, FL 32855-5837
- McDonnell Douglas Astronautic
 ATTN: Nikolai A. Louie
 5301 Bolsa Ave.
 Huntington Beach, CA 92647
- McDonnell Douglas, Inc. ATTN: David Hamilton P.O. Box 516
 St. Louis, MO 63166
- McDonnell Douglas, Inc.
 ATTN: Alan R. Parker
 3855 Lakewood Blvd., MC 35-18
 Long Beach, CA 90846
- NFK Engineering, Inc.
 ATTN: Dr. Michael P. Pakstys
 4200 Wilson Blvd.
 Arlington, VA 22203-1800
- NASA-Ames Research Center ATTN: Dr. Alex Woo MS 227-2 Moffett Field, CA 94035-1000
- NASA-Ames Research Center ATTN: Leroy Presley MS 227-4 Moffett Field, CA 94035-1000
- NAVIR DEVCON
 ATTN: Frank Wenograd, Code 6043
 Walminstor, PA 18974

- Oklahoma State University
 College of Engineering, Architecture
 and Technology
 ATTN: Thomas M. Browder, Jr.
 P.O. Box 1925
 Eglin AFB, FL 32542
- 1 Rome Air Development Center ATTN: RADC/IRRE, Peter J. Costianes Griffis Air Force Base, NY 13441-5700
- Rome Air Development Center RADC/OCTM
 ATTN: Edward Starczewski
 Building 106
 Griffis Air Force Base, NY 13441-5700
- 1 SAIC ATTN: Dr. Alan J. Toepfer 2301 Yale Blvd., SE Albuquerque, NM 87106
- 1 SAIC ATTN: Terry Keller Suite 200 1010 Woodman Drive Dayton, OH 45432
- 1 SAIC
 ATTN: David R. Garfinkle
 Malibu Canyon Business Park
 26679 W. Agoura Road, Suite 200
 Calabasas, CA 91302
- 1 George Sharp Company
 ATTN: Dennis M. McCarley
 2121 Crystal Drive
 Suite 714
 Arlington, VA 22202
- Sidwell-Ross and Associates, Inc.
 ATTN: LTG Marion C. Ross, (USA Ret)

 Executive Vice President

 P.O. Box 88531

 Atlanta, GA 30338
- Sigma Research, Inc.
 ATTN: Dr. Richard Bossi
 4014 Hampton Way
 Kent, WA 98032

- 1 Southwest Research Institute ATTN: Martin Goland P.O. Drawer 28255 San Antonio, TX 78228-0255
- 1 Sparta, Inc. ATTN: David M. McKinley 4901 Corporate Drive Huntsville, AL 35805-6201
- SRI International
 ATTN: Donald R. Curran
 333 Ravenswood Ave.
 Menlo Park, CA 94025
- Star Laboratory, Stanford University Electrical Engineering Department ATTN: Dr. Joseph W. Goodman 233 Durand Building Stanford, CA 94305-4055
- 1 TASC
 ATTN: Richard E. Kinsler
 1992 Lewis Turner Boulevard
 Fort Walton Beach, FL 32548-1255
- TASC
 ATTN: COL James Logan (Ret)
 1101 Wilson Blvd.
 Suite 1500
 Arlington, VA 22209
- 1 Teledyne Brown Engineering ATTN: John W. Wolfsberger, Jr. Cummings Research Park 300 Sparkman Drive, NW P.O. Box 070007 Huntsville, AL 35807-7007
- United Technologies Corporation Advanced Systems Division ATTN: Richard J. Holman 10180 Telesis Court San Diego, CA 92121
- 1 The Johns Hopkins University Applied Physics Laboratory ATTN: Jonathan Fluss Johns Hopkins Road Laurel, MD 20707

No. of No. of Copies Organization Copies Organization LTV Missiles and Electronics Group Mr. William M. Hubbard. ATTN: Roger W. Melin ASB Consultant P.O. Box 650003 613 Eastlake Drive Columbia, MO 65203 **MS EM-36** Dallas, TX 75265-0003 1 Mr. Charles E. Joachim, Wackenhut Applied Technologies Center **DA Consultant** 1 ATTN: Robert D. Carpenter P.O. Box 631 10530 Rosehaven St. Vicksburg, MS 39180 Suite 500 Fairfax, VA 22030-2877 Dr. Edward R. Jones, DA Consultant 9881 Wild Deer Road 1 Westinghouse ATTN: Harvey Klochn St. Louis, MO 63124 Box 1693 MS 8530 MG Robert Kirwan (USA Ret), Baltimore, MD 21203 **DA** Consultant 10213 Grovewood Way **SURVICE Engineering** Fairfax, VA 22032 ATTN: Jim Foulk Dir. TEXCOM FSTP George Large 1 ATTN: STE-TFS-Z, Donald J. Kreicarek Glenn Gillis Kris Keller Ft. Sill. OK 73503-6100 Suite 103 1003 Old Philadelphia Road Mr. Robert B. Kurtz. Aberdeen, MD 21001 **DA Consultant** 542 Merwins Lane 1 Georgia Institute of Technology Fairfield, CT 06430-1920 ATTN: Dr. Richard Moore ECSL/EME 1 LTGEN Howard W. Leaf ERB Building, Room 111 USAF (Retired) Atlanta, GA 30332 8504 Brook Road McLean, VA 22101 1 Georgia Institute of Technology ATTN: Dr. L.G. Callahan, Jr. Dr. Roy A. Lucht School of Industrial & Systems Engineering Group M-B, MS-J960 765 Ferst Drive Los Alamos, NM 87545 Atlanta, GA 30332-0385 Mr. Donald F. Menne, 1 Mr. Abraham Golub, DA Consultant **DA** Consultant 617 Foxcroft Drive 203 Yoakum Parkway, Apt. 607 Bel Air, MD 21014 Alexandria, VA 22304 Mr. Richard C. Messinger Vice President and Chief Technical 1 Mr. Dave Hardison, ASB Consultant Officer 3807 Bent Branch Road Cincinnati Mailacron, Inc.

Cincinnati, OH 45209

Falls Church, VA 22041

- 1 GEN Glenn Otis USA (Ret)
 Coleman Research Corporation
 5950 Lakehurst Dr.
 Orlando, FL 32819
- MG Peter G. Olenchuk (USA Ret), BAST Consultant 6801 Baron Road McLean, VA 22101
- Mr. Albert E. Papazoni,
 DA Consultant
 1600 Surrey Hill Drive
 Austin, TX 78746-7338
- Harry Reed, Sr.,
 Battelle Consultant
 138 Edmund St.
 Aberdeen, MD 21001
- 1 Dr. A.E. Schmidlin, DA Consultant 28 Highview Road Caldwell, NJ 07006-5502
- Mr. Robert G.S. Sewell
 1236 Mt. Whitney lane
 Ridgecrest, CA 93555
- 1 MIMEX Corporation ATTN: Mr. Charles S. Smith 9 Doaks Lane Marblehead, MA 01945
- Mr. Arthur Stein,
 BAST Consultant
 Chapel Woods Court
 Williamsville, NY 14221-1816
- Dr. Dora Strother,
 ASB Consultant
 3616 Landy Lane
 Fort Worth, TX 76118
- 1 Mr. Charles F. Tiffany 9 Westerly Lane Centerville, OH 45458

No. of Copies Organization

Aberdeen Proving Ground

- Dir, USAMSAA
 ATTN: AMXSY-A, W. Clifford
 AMXSY-C, A. Reid
 AMXSY-CR, M. Miller
 AMXSY-G,
 J. Kramar
 G. Comstock
 AMXSY-GA, W. Brooks
 AMXSY-J, A. LaGrange
 AMXSY-L, J. McCarthy
 AMXSY-RA, R. Scungio
- 5 Cdr, USATECOM
 ATTN: AMSTE-CG
 AMSTE-TA-L,
 A. Yankolonis
 N. Harrington
 S. Grill
 AMSTE-TC-C, R. Cozby
- 1 Cdr, CBDA ATTN: SCBRD-RTC, P. Grasso
- 4 Cdr, USAOC&S
 ATTN: ATSL-DES
 ATSL-DTD-CM
 ATSL-CD-TE
 ATSL-CD-BDAR (Hoy)

INTENTIONALLY LEFT BLANK.

USER EVALUATION SHEET/CHANGE OF ADDRESS

	CODE DVADORITOR S	HEBITCHANGE OF ADD	, KIJOO
This Laboratory comments/answe	undertakes a continuing effort trs to the items/questions below	to improve the quality of th will aid us in our efforts.	e reports it publishes. Your
1. ARL Report N	fumber ARL-TR-149	Date of Report_	June 1993
2. Date Report Ro	eceived		
_	ort satisfy a need? (Comment will be used.)		
4. Specifically, ideas, etc.)	how is the report being used?	(Information source, desig	n data, procedure, source of
	mation in this report led to any c voided, or efficiencies achieved,		s man-hours or dollars saved,
	nments. What do you think shization, technical content, forma		ve future reports? (Indicate
	Organization		
CURRENT	Name		····
ADDRESS	Street or P.O. Box No.		
	City, State, Zip Code		
	Change of Address or Address ld or Incorrect address below.	Correction, please provide the	he Current or Correct address
	Organization		
OLD	Name		
ADDRESS	Street or P.O. Box No.		

City, State, Zip Code

(Remove this sheet, fold as indicated, tape closed, and mail.)
(DO NOT STAPLE)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS

BUSINESS REPLY MAIL

FIRST CLASS PERMIT No 8001, APG, MO

Postage will be paid by addressee

Director
U.S. Army Research Laboratory
ATTN: AMSRL-OP-CI-B (Tech Lib)
Aberdeen Proving Ground, MD 21005-5066

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES